

Hydraulic Oil

Anti-Wear Oil for Industrial & Mobil Applications

Formulated to deliver excellent performance in a range of hydraulic components used on systems subjected to moderate operating conditions.

Product Description:

Maritime Fuels Plus Hydraulic Oils provide good anti-wear protection reducing wear in pumps and actuators in open or closed-loop systems. Their optimal resistance to oxidation and thermal degradation helps reduce the formation of deposits and varnish. Maritime Fuels Plus Hydraulic Oils offer the following benefits:

- Anti-wear protection helping improve component life
- Resistance to oxidation helping to reduce deposit formation
- Water separation properties allow easy removal of water from systems helping reduce potential damage to system components

Product Features:

Physical & Chemical Properties

Maritime Fuels Plus Hydraulic Oil	22	32	46	68
<i>Physical State</i>	Liquid			
<i>Colour</i>	Amber			
<i>Odor</i>	Characteristic			
<i>ISO Viscosity Grade</i>	22	32	46	68
<i>cSt @ 40°C</i>	22	32	46	68
<i>cSt @ 100°C</i>	4.3	5.4	6.7	8.6
<i>Viscosity Index ASTM D 2270</i>	101	102	100	99
<i>Pour Point ASTM D 97</i>	-36	-33	-30	-27
<i>Flash Point ASTM D 92</i>	202 (396)	206 (403)	218 (424)	222 (432)
<i>Rust ASTM D 665 B</i>	Pass	Pass	Pass	Pass

**The information contained herein is subject to change without notification.*

Applications:

- Fluid power systems
- Hydraulic systems using gear, vane and piston pumps
- Hydraulic pumps and components requiring anti-wear fluids

Health & Safety:

Based on the current description as well as the available information, this product is not expected to produce adverse effects on health when used for its intended application in conjunction with the recommendations provided in the Material Safety Data Sheet (MSDS).

Material Safety Data Sheets are available upon request through your sales contract office, or at www.maritimefuels.ca

Environmental Safety:

Please recycle this product container and remaining oil in appropriate facilities.